

ITEM: 52RM87 - Flexible Lighter Butane Easy To Us

SDS: E3811

ORDER: 0170231475

LP NUMBER: U877742251

SAFETY DATA SHEET (SDS)

This SDS should be attached or kept with the respective product with which it is associated.

SDS - E3811

Associated Grainger Items
52RM87, 56YY29

W
WORTHINGTON CYLINDER

SAFETY DATA SHEET

1. IDENTIFICATION

PRODUCT IDENTIFIER: BUTANE

OTHER MEANS OF IDENTIFICATION:

SDS NUMBER: WC026

RECOMMENDED USE: HAND TORCH FUEL

RECOMMENDED RESTRICTIONS: NONE KNOWN.

MANUFACTURER/IMPORTER/SUPPLIER/DISTRIBUTOR INFORMATION:

MANUFACTURER/SUPPLIER: WORTHINGTON CYLINDER CORPORATION

ADDRESS:
200 OLD WILSON BRIDGE ROAD
COLUMBUS, OH 43085
UNITED STATES

EMAIL: CYLINDERS@WORTHINGTONINDUSTRIES.COM

TELEPHONE NUMBER: 866-928-2657

CHEMTREC - 24 HOURS:
WITHIN US AND CANADA: 800-424-9300
OUTSIDE US AND CANADA: +1 703-741-5970 (COLLECT CALLS ACCEPTED)

2. HAZARD(S) IDENTIFICATION

PHYSICAL HAZARDS:
FLAMMABLE GASES: CATEGORY 1
GASES UNDER PRESSURE: LIQUEFIED GAS

HEALTH HAZARDS: NOT CLASSIFIED.

OSHA DEFINED HAZARDS: NOT CLASSIFIED.

LABEL ELEMENTS:
FLAME
GAS CYLINDER

SIGNAL WORD: DANGER

HAZARD STATEMENT:
EXTREMELY FLAMMABLE GAS. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

PRECAUTIONARY STATEMENT:

PREVENTION:
KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

RESPONSE:
LEAKING GAS FIRE:
DO NOT EXTINGUISH, UNLESS LEAK CAN BE STOPPED SAFELY. ELIMINATE ALL IGNITION SOURCES IF SAFE TO DO SO.

STORAGE: PROTECT FROM SUNLIGHT. STORE IN A WELL-VENTILATED PLACE.

DISPOSAL:
DISPOSE OF WASTE AND RESIDUES IN ACCORDANCE WITH LOCAL AUTHORITY REQUIREMENTS.

HAZARD(S) NOT OTHERWISE CLASSIFIED (HNOC):
MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

3. COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES:

CHEMICAL NAME	CAS NUMBER	%
ISOBUTANE	75-28-5	60-80
BUTANE	106-97-8	20-40

4. FIRST-AID MEASURES

INHALATION:
MOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND WASH SKIN WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS AND PERSISTS. IF FROSTBITE OCCURS, IMMERSE INVOLVED AREA IN WARM WATER (BETWEEN 100 DEG. F/38 DEG. C AND 110 DEG. F/43 DEG. C, NOT EXCEEDING 112 DEG. F/44 DEG. C). KEEP IMMERSED FOR 20 TO 40 MINUTES. SEEK MEDICAL ASSISTANCE.

EYE CONTACT:
IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

INGESTION IS NOT A TYPICAL ROUTE OF EXPOSURE FOR GASES OR LIQUEFIED GASES.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:
EXPOSURE TO RAPIDLY EXPANDING GAS OR VAPORIZING LIQUID MAY CAUSE FROSTBITE ("COLD BURN"). VERY HIGH EXPOSURE CAN CAUSE SUFFOCATION FROM LACK OF OXYGEN. MAY CAUSE DROWSINESS OR DIZZINESS.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:
EXPOSURE MAY AGGRAVATE PRE-EXISTING RESPIRATORY DISORDERS. TREAT SYMPTOMATICALLY.

GENERAL INFORMATION:

ENSURE THAT MEDICAL PERSONNEL ARE AWARE OF THE MATERIAL(S) INVOLVED, AND TAKE PRECAUTIONS TO PROTECT THEMSELVES.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, WATER SPRAY, FOG, OR FOAM.

UNSUITABLE EXTINGUISHING MEDIA: FULL WATER JET.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:
SELECTION OF RESPIRATORY PROTECTION FOR FIREFIGHTING: FOLLOW THE GENERAL FIRE PRECAUTIONS INDICATED IN THE WORKPLACE.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:
SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING MUST BE WORN IN CASE OF FIRE.

FIRE FIGHTING EQUIPMENT/INSTRUCTIONS:

MOVE CONTAINER FROM FIRE AREA IF IT CAN BE DONE WITHOUT RISK.

DO NOT EXTINGUISH FIRES UNLESS GAS FLOW CAN BE STOPPED SAFELY; EXPLOSIVE RE-IGNITION MAY OCCUR. PROMPTLY ISOLATE THE SCENE BY REMOVING ALL PERSONS FROM THE VICINITY OF THE INCIDENT. NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. FOR FIRES INVOLVING THIS MATERIAL, DO NOT ENTER ANY ENCLOSED OR CONFINED FIRE SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS. STOP FLOW OF MATERIAL. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL AND TO PROTECT PERSONNEL EFFECTING SHUTOFF. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS AND TO PROTECT PERSONNEL ATTEMPTING TO STOP LEAK. PREVENT RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING STREAMS, SEWERS OR DRINKING WATER SUPPLY.

SPECIFIC METHODS:
USE STANDARD FIREFIGHTING PROCEDURES AND CONSIDER THE HAZARDS OF OTHER INVOLVED MATERIALS.

GENERAL FIRE HAZARDS: EXTREMELY FLAMMABLE GAS.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

EVACUATE THE AREA PROMPTLY. NO ACTION SHALL BE TAKEN INVOLVING ANY PERSONAL RISK OR WITHOUT SUITABLE TRAINING. KEEP UNNECESSARY PERSONNEL AWAY.

ENSURE ADEQUATE VENTILATION. IN CASE OF INADEQUATE VENTILATION, USE RESPIRATORY PROTECTION. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT (SEE SECTION 8).

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

VENTILATE WELL, STOP FLOW OF GAS OR LIQUID IF POSSIBLE. IMMEDIATELY CONTACT EMERGENCY PERSONNEL.

FOR WASTE DISPOSAL, SEE SECTION 13 OF THE SDS.

ENVIRONMENTAL PRECAUTIONS:
DO NOT BE RELEASED INTO THE ENVIRONMENT. PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. PREVENT FROM ENTERING INTO SOIL, DITCHES, SANITARY SEWERS, WATERWAYS AND/OR GROUNDWATER.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

DO NOT HANDLE, STORE OR OPEN NEAR AN OPEN FLAME, SOURCES OF HEAT OR SOURCES OF IGNITION. PROTECT MATERIAL FROM DIRECT SUNLIGHT. DO NOT SMOKE. ALL EQUIPMENT USED WHEN HANDLING THE PRODUCT MUST BE GROUNDED. USE ONLY WITH ADEQUATE VENTILATION. DO NOT BREATHE GAS. DO NOT GET IN EYES, ON SKIN, ON CLOTHING. AVOID PROLONGED EXPOSURE. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES. KEEP AWAY FROM HEAT, SPARK, OPEN FLAMES AND OTHER SOURCES OF IGNITION.

WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT (SEE SECTION 8). EATING, DRINKING, AND SMOKING SHOULD BE PROHIBITED IN AREAS WHERE THIS MATERIAL IS HANDLED, STORED, AND PROCESSED. RISK OF VAPOR CONCENTRATION ON THE FLOOR AND IN LOW-LYING AREAS.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
DO NOT STORE, INCINERATE, OR HEAT THIS MATERIAL ABOVE 120 DEGREES FAHRENHEIT. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. THIS MATERIAL CAN ACCUMULATE STATIC CHARGE WHICH MAY CAUSE SPARK AND BECOME AN IGNITION SOURCE. PREVENT ELECTROSTATIC CHARGE BUILD-UP BY USING COMMON BONDING AND GROUNDING TECHNIQUES. STORE IN A COOL, DRY PLACE OUT OF DIRECT SUNLIGHT. SECURE CYLINDERS IN AN UPRIGHT POSITION AT ALL TIMES. CLOSE ALL VALVES WHEN NOT IN USE. STORE IN A WELL-VENTILATED PLACE. STORE AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION 10 OF THE SDS). STORE IN ACCORDANCE WITH LOCAL, REGIONAL, NATIONAL, AND INTERNATIONAL REGULATIONS. KEEP CONTAINER TIGHTLY CLOSED AND SEALED UNTIL READY FOR USE. PROTECT CYLINDERS FROM DAMAGE.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS:

US. ACGIH THRESHOLD LIMIT VALUES:

COMPONENTS	TYPE	VALUE
BUTANE (CAS 106-97-8)	STEL	1000 PPM
ISOBUTANE (CAS 75-28-5)	STEL	1000 PPM

US. NIOSH: POCKET GUIDE TO CHEMICAL HAZARDS

COMPONENTS	TYPE	VALUE
BUTANE (CAS 106-97-8)	TWA	1900 MG/M3 800 PPM
ISOBUTANE (CAS 75-28-5)	TWA	1900 MG/M3 800 PPM

BIOLOGICAL LIMIT VALUES:

NO BIOLOGICAL EXPOSURE LIMITS NOTED FOR THE INGREDIENT(S).

EXPOSURE GUIDELINES: FOLLOW STANDARD MONITORING PROCEDURES.

APPROPRIATE ENGINEERING CONTROLS:
PROVIDE ADEQUATE VENTILATION. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: WEAR APPROVED SAFETY GLASSES OR GOGGLES.

SKIN PROTECTION:

HAND PROTECTION: WEAR APPROPRIATE CHEMICAL RESISTANT GLOVES.

OTHER: WEAR PROTECTIVE CLOTHING APPROPRIATE FOR THE RISK OF EXPOSURE.

RESPIRATORY PROTECTION:
IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS (WHERE APPLICABLE) OR TO AN ACCEPTABLE LEVEL (IN COUNTRIES WHERE EXPOSURE LIMITS HAVE NOT BEEN ESTABLISHED), AN APPROVED RESPIRATOR MUST BE WORN.

THERMAL HAZARDS:
CONTACT WITH LIQUEFIED GAS MIGHT CAUSE FROSTBITES, IN SOME CASES WITH TISSUE DAMAGE. WEAR APPROPRIATE THERMAL PROTECTIVE CLOTHING, WHEN NECESSARY.

GENERAL HYGIENE CONSIDERATIONS:
DO NOT EAT, DRINK OR SMOKE WHEN USING THE PRODUCT. WASH THOROUGHLY AFTER HANDLING. PROVIDE EYEWASH STATION AND SAFETY SHOWER. HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

PHYSICAL STATE: GAS (LIQUEFIED).

FORM: COMPRESSED LIQUEFIED GAS.

COLOR: COLORLESS.

ODOR: FAINT, GASOLINE-LIKE.

ODOR THRESHOLD: NOT AVAILABLE.

PH: NOT AVAILABLE.

MELTING POINT/FREEZING POINT: -216.76 DEG. F (-138.2 DEG. C)

INITIAL BOILING POINT AND BOILING RANGE: -11.7 DEG. F (-24.28 DEG. C)

FLASH POINT: -76.3 DEG. F (-60.2 DEG. C)

EVAPORATION RATE: NOT AVAILABLE.

FLAMMABILITY (SOLID, GAS): FLAMMABLE GAS.

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

FLAMMABILITY LIMIT - LOWER (%): 1.8%

FLAMMABILITY LIMIT - UPPER (%): 8.4%

VAPOR PRESSURE: 28 PSIG (APPROXIMATE)

VAPOR DENSITY: >2 (AIR = 1)

RELATIVE DENSITY: 0.57 (H₂O = 1)

SOLUBILITY (IES):

SOLUBILITY (WATER): <0.1% IN WATER AT 70 DEG. F

PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT AVAILABLE.

AUTO-IGNITION TEMPERATURE: 548.33 DEG. F (286.85 DEG. C)

DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

VISCOSITY: NOT AVAILABLE.

OTHER INFORMATION:

MOLECULAR FORMULA: C₄-H₁₀

MOLECULAR WEIGHT: 58.12 G/MOL

PERCENT VOLATILE: 100%

10. STABILITY AND REACTIVITY

REACTIVITY:
THE PRODUCT IS NON-REACTIVE UNDER NORMAL CONDITIONS OF USE, STORAGE AND TRANSPORT.

CHEMICAL STABILITY:
STABLE UNDER NORMAL TEMPERATURE CONDITIONS AND RECOMMENDED USE.

POSSIBILITY OF HAZARDOUS REACTIONS:

POLYMERIZATION WILL NOT OCCUR. MAY FORM EXPLOSIVE MIXTURE WITH AIR. THIS PRODUCT MAY REACT WITH OXIDIZING AGENTS.

CONDITIONS TO AVOID: HEAT, FLAMES AND SPARKS.

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS. STRONG ACIDS. HALOGENS.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES. HYDROCARBONS.

11. TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE:

INHALATION:

HIGH CONCENTRATIONS:

SUFFOCATION (ASPHYXIA) HAZARD - IF ALLOWED TO ACCUMULATE TO CONCENTRATIONS THAT REDUCE OXYGEN BELOW SAFE BREATHING LEVELS. BREATHING OF HIGH CONCENTRATIONS MAY CAUSE DIZZINESS, LIGHT-HEADEDNESS, HEADACHE, NAUSEA AND LOSS OF COORDINATION. CONTINUED INHALATION MAY RESULT IN UNCONSCIOUSNESS.

SKIN CONTACT: CONTACT WITH LIQUEFIED GAS MAY CAUSE FROSTBITE.

EYE CONTACT: CONTACT WITH LIQUEFIED GAS MAY CAUSE FROSTBITE.

INGESTION: NOT LIKELY, DUE TO THE FORM OF THE PRODUCT.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

EXPOSURE TO RAPIDLY EXPANDING GAS OR VAPORIZING LIQUID MAY CAUSE FROSTBIT ("COLD BURN"). VERY HIGH EXPOSURE CAN CAUSE SUFFOCATION FROM LACK OF OXYGEN. MAY CAUSE DROWSINESS OR DIZZINESS.

INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

HIGH CONCENTRATION:

SUFFOCATION (ASPHYXIA) HAZARD - IF ALLOWED TO ACCUMULATE TO CONCENTRATIONS THAT REDUCE OXYGEN BELOW SAFE BREATHING LEVELS.

SKIN CORROSION/IRRITATION:

CONTACT WITH LIQUEFIED GAS MIGHT CAUSE FROSTBITES, IN SOME CASES WITH TISSUE DAMAGE.

SERIOUS EYE DAMAGE/EYE IRRITATION:

DIRECT CONTACT WITH LIQUEFIED GAS MAY CAUSE EYE DAMAGE FROM FROSTBITE.

RESPIRATORY OR SKIN SENSITIZATION:

RESPIRATORY SENSITIZATION: NOT CLASSIFIED.

SKIN SENSITIZATION: NOT CLASSIFIED.

GERM CELL MUTAGENICITY: NOT CLASSIFIED.

CARCINOGENICITY: NOT CLASSIFIED.

OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1001-1050): NOT LISTED.

REPRODUCTIVE TOXICITY: NOT CLASSIFIED.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: NOT CLASSIFIED.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: NOT CLASSIFIED.

ASPIRATION HAZARD: NOT CLASSIFIED.

CHRONIC EFFECTS: MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS.

12. ECOLOGICAL INFORMATION

ECOTOXICITY: NOT EXPECTED TO BE HARMFUL TO AQUATIC ORGANISMS.

PERSISTENCE AND DEGRADABILITY: THE PRODUCT IS READILY BIODEGRADABLE.

BIOACCUMULATIVE POTENTIAL: THE PRODUCT IS NOT EXPECTED TO BIOACCUMULATE.

PARTITION COEFFICIENT N-OCTANOL / WATER (LOG KOW):

BUTANE (CAS 106-97-8): 2.89

ISOBUTANE (CAS 75-28-5): 2.76

MOBILITY IN SOIL: MAY EVAPORATE QUICKLY.

MOBILITY IN GENERAL: MAY EVAPORATE QUICKLY.

OTHER ADVERSE EFFECTS: NONE KNOWN.

13. DISPOSAL CONSIDERATIONS

DISPOSAL INSTRUCTIONS:

USE THE CONTAINER UNTIL EMPTY. DO NOT DISPOSE OF ANY NON-EMPTY CONTAINER. EMPTY CONTAINERS HAVE RESIDUAL VAPOR THAT IS FLAMMABLE AND EXPLOSIVE. CYLINDERS SHOULD BE EMPTIED AND RETURNED TO A HAZARDOUS WASTE COLLECTION POINT. DO NOT PUNCTURE OR INCINERATE EVEN WHEN EMPTY. DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

LOCAL DISPOSAL REGULATIONS:

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

HAZARDOUS WASTE CODE:

D001: WASTE FLAMMABLE MATERIAL WITH A FLASH POINT <140 DEG. F

WASTE FROM RESIDUES / UNUSED PRODUCTS:

DISPOSE OF IN ACCORDANCE WITH LOCAL REGULATIONS.

CONTAMINATED PACKAGING:

SINCE EMPTIED CONTAINERS MAY RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

14. TRANSPORT INFORMATION

DOT:

UN NUMBER: UN1011

UN PROPER SHIPPING NAME: BUTANE

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

SUBSIDIARY RISK:

LABEL(S): 2.1

PACKING GROUP: NOT APPLICABLE.

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

SPECIAL PROVISIONS: 19, T50

PACKAGING EXCEPTIONS: 306

PACKAGING NON BULK: 304

PACKAGING BULK: 314, 315

IATA:

UN NUMBER: UN1011

UN PROPER SHIPPING NAME: BUTANE

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

SUBSIDIARY RISK:

LABEL(S): 2.1

PACKING GROUP: NOT APPLICABLE.

ENVIRONMENTAL HAZARDS: NO.

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

IMDG:

UN NUMBER: UN1011

UN PROPER SHIPPING NAME: BUTANE

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

SUBSIDIARY RISK:

LABEL(S): 2.1

PACKING GROUP: NOT APPLICABLE.

ENVIRONMENTAL HAZARDS:

MARINE POLLUTANT: NO.

EMS: F-D, S-U

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:
NOT APPLICABLE.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS:

THIS PRODUCT IS A "HAZARDOUS CHEMICAL" AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

ALL COMPONENTS ARE ON THE U.S. EPA TSCA INVENTORY LIST.

TSCA SECTION 12(B) EXPORT NOTIFICATION (40 CFR 707, SUBPT. D):
NOT REGULATED.

OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1001-1050): NOT LISTED.

CERCLA HAZARDOUS SUBSTANCE LIST (40 CFR 302.4):
BUTANE (CAS 106-97-8): LISTED
ISOBUTANE (CAS 75-28-5): LISTED

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA):

HAZARD CATEGORIES:
IMMEDIATE HAZARD: NO
DELAYED HAZARD: NO
FIRE HAZARD: YES
REACTIVITY HAZARD: NO
PRESSURE HAZARD: YES

SARA 302 EXTREMELY HAZARDOUS SUBSTANCE: NOT LISTED.

SARA 311/312 HAZARDOUS CHEMICAL: YES

SARA 313 (TRI REPORTING): NOT REGULATED.

OTHER FEDERAL REGULATIONS:

CLEAN AIR ACT (CAA) SECTION 112 HAZARDOUS AIR POLLUTANTS (HAPS) LIST:
NOT REGULATED.

CLEAN AIR ACT (CAA) SECTION 112(R) ACCIDENTAL RELEASE PREVENTION
(40 CFR 68.130):
BUTANE (CAS 106-97-8)
ISOBUTANE (CAS 75-28-5)

SAFE DRINKING WATER ACT (SDWA): NOT REGULATED.

US STATE REGULATIONS:

US. MASSACHUSETTS RTK - SUBSTANCE LIST:
BUTANE (CAS 106-97-8)
ISOBUTANE (CAS 75-28-5)

US. NEW JERSEY WORKER AND COMMUNITY RIGHT-TO-KNOW ACT:
BUTANE (CAS 106-97-8)
ISOBUTANE (CAS 75-28-5)

US. PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW LAW:
BUTANE (CAS 106-97-8)
ISOBUTANE (CAS 75-28-5)

US. RHODE ISLAND RTK:
BUTANE (CAS 106-97-8)
ISOBUTANE (CAS 75-28-5)

US. CALIFORNIA PROPOSITION 65:
CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986
(PROPOSITION 65): THIS MATERIAL IS NOT KNOWN TO CONTAIN ANY CHEMICALS
CURRENTLY LISTED AS CARCINOGENS OR REPRODUCTIVE TOXINS.

INTERNATIONAL INVENTORIES:

COUNTRY(S) OR REGION	INVENTORY NAME	ON INVENTORY (YES/NO) *
----------------------	----------------	----------------------------

CANADA	DOMESTIC SUBSTANCES LIST (DSL)	YES
--------	--------------------------------	-----

CANADA	NON-DOMESTIC SUBSTANCES LIST (NDL)	YES
--------	------------------------------------	-----

UNITED STATES & PUERTO RICO	TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY	YES
--------------------------------	--	-----

*A "YES" INDICATES THIS PRODUCT COMPLIES WITH THE INVENTORY REQUIREMENTS
ADMINISTERED BY THE GOVERNING COUNTRY(S).

A "NO" INDICATES THAT ONE OR MORE COMPONENTS OF THE PRODUCT ARE NOT LISTED
OR EXEMPT FROM LISTING ON THE INVENTORY ADMINISTERED BY THE GOVERNING
COUNTRY(S).

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

ISSUE DATE: 28-MAY-2015

REVISION DATE:

VERSION #: 01

FURTHER INFORMATION:

HAZARD SCALE:
0 = MINIMAL
1 = SLIGHT
2 = MODERATE
3 = SERIOUS
4 = SEVERE

HMS(R*) RATINGS:
HEALTH 1
FLAMMABILITY 4
PHYSICAL HAZARD 1

NFPA RATINGS:
1
4
1

DISCLAIMER:
ALL INFORMATION IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE
ACCURATE AND RELIABLE. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND IS
MADE WITH REGARD TO THE ACCURACY OF INFORMATION OR THE SUITABILITY OF THE
RECOMMENDATIONS CONTAINED HEREIN. IT IS THE USER'S RESPONSIBILITY TO
ASSESS THE SAFETY AND TOXICITY OF THIS PRODUCT UNDER THEIR OWN CONDITIONS
OF USE AND TO COMPLY WITH ALL APPLICABLE LAWS AND REGULATIONS.
WORTHINGTON CYLINDER CORPORATION CANNOT ANTICIPATE ALL CONDITIONS UNDER
WHICH THIS INFORMATION AND ITS PRODUCT, OR THE PRODUCTS OF OTHER
MANUFACTURERS IN COMBINATION WITH ITS PRODUCT, MAY BE USED. IT IS THE
USER'S RESPONSIBILITY TO ENSURE SAFE CONDITIONS FOR HANDLING, STORAGE AND
DISPOSAL OF THE PRODUCT, AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE
OR EXPENSE DUE TO IMPROPER USE. THE INFORMATION IN THE SHEET WAS WRITTEN
BASED ON THE BEST KNOWLEDGE AND EXPERIENCE CURRENTLY AVAILABLE.

911467

SDS US